


UD Carbone Tissé 200g/m² 50mm 12K HR

CARACTERISTIQUES / CHARACTERISTICS		NOMINAL	TOLERANCE
Poids total / Mass per unit area	g/m ²	204	± 5%
Armure / Weave		Carbone Tissé / Woven carbon	
Compatibilité/ Compatibility		Epoxy	

CONSTRUCTION		CHAINE / WARP	TRAME / WEFT
Nature de la Fibre / Fiber description		Carbon 12K HR	Thermoplastic
		800 tex	24 tex
distribution du poids / Weight distribution	g/m ²	202	2
	%	99	1

CONDITIONNEMENT / PACKAGING		NOMINAL
Largeur standard / Standard width	mm	50
Longueur approx/ Approx length	ml	125
Poids rouleau / Roll weight	kg	1,27



LEGAL NOTES: SICOMIN reserves the right to change the properties of its products. All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data and tolerance may vary due to circumstances beyond our control. No warranties of any kind are made except that the materials supplied are of standard quality. All risk and liabilities arising from handling, storage and use of products, as well as compliance with applicable legal restrictions, rests with the user.

MENTIONS LÉGALES : SICOMIN se réserve le droit de modifier les propriétés du produit. Toutes les caractéristiques spécifiées dans cette Fiche technique sont basées sur des tests de laboratoire. Les mesures et leurs tolérances effectives peuvent varier pour différentes raisons. SICOMIN se réserve le droit Aucune garantie de quelque nature que ce soit, sauf que les matériaux fournis sont de qualité standard. Tous les risques et responsabilités découlant de la manutention, le stockage et l'utilisation des produits, ainsi que le respect des restrictions légales applicables, incombe à l'utilisateur.